Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS. 2. REPORT TYPE 1. REPORT DATE (DD-MM-YYYY) 3. DATES COVERED (From - To) Technical Paper 4. TITLE AND SUBTITLE 5a. CONTRACT NUMBER **5b. GRANT NUMBER** alla chen 5c. PROGRAM ELEMENT NUMBER 5d. PROJECT NUMBER 6. AUTHOR(S) 1011 5e. TASK NUMBER 0046 **5f. WORK UNIT NUMBER** 346 20 4 8. PERFORMING ORGANIZATION 7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) REPORT 9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) 10. SPONSOR/MONITOR'S ACRONYM(S) Air Force Research Laboratory (AFMC) 11. SPONSOR/MONITOR'S AFRL/PRS NUMBER(S) 5 Pollux Drive Edwards AFB CA 93524-7048 12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited. 13. SUPPLEMENTARY NOTES 14. ABSTRACT 20030116 035 15. SUBJECT TERMS 16. SECURITY CLASSIFICATION OF: 19a. NAME OF RESPONSIBLE 17. LIMITATION 18. NUMBER OF ABSTRACT **OF PAGES PERSON** Leilani Richardson a. REPORT b. ABSTRACT c. THIS PAGE 19b. TELEPHONE NUMBER (include area code) Α (661) 275-5015 Unclassified Unclassified Unclassified Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. 239.18

REPORT DOCUMENTATION PAGE

Form Approved

OMB No. 0704-0188

FROM: PROI (TI) (STINFO)

24 Apr 2000

SUBJECT: Authorization for Release of Technical Information, Control Number: AFRL-PR-ED-TP-2000-086 I. Ismail (ERC), T. Hawkins, "Adiabatic Compression Sensitivity of Liquid Fuels and Monopropellants"

46th International Instrumentation Symposium (Statement A) (Submission Deadline: 24 Apr 2000) (Bellevue, WA, 30 Apr-04 May 2000)

b.) military/national critical technology, c.) exp	on, and e.) technical sensitivity and/or economic sensitivity.
Signature	Date
2. This request has been reviewed by the Public and/or b) possible higher headquarters review. Comments:	Affairs Office for: a.) appropriateness for public release
Signature	Date
) military/national critical technology, d.) economic sensitivity,) format and completion of meeting clearance form if required
Signature	Date
	- · · · · · · · · · · · · · · · · · · ·
	APPROVED/APPROVED AS AMENDED/DISAPPROVEI
	ROBERT C. CORLEY (Date) Senior Scientist (Propulsion)

Propulsion Directorate


Adiabatic Compression Sensitivity of Liquid Fuels and Monopropellants

Ismail M. K. Ismail
ERC, Inc.
c/o AFRL/PRSP
Edwards Air Force Base, CA 93524


Tom W. Hawkins
AFRL/PRSP
Edwards Air Force Base, CA 93524

CONCERN

Rapid compression results from mechanical shocks to reservoir, from rapid opening/closing of valves and from engine combustion instability.



CONCEPT of Adiabatic Compression



BACKGROUND


- Aerojet (1971-1980) tested adiabatic compressibility of hydrazine and propellants using 316-SS, 304L-SS and other alloys.
- They tested at two compression ratios: 32:1 and 79:1.
- They found that the threshold temperature for different liquids was 90 -100 °C.
- NASA Report (1978): No standard procedure has been published.
- selected conservatively two test conditions for shuttle Operations: Hazards Research Corporation/Sundstrand Aviation (1975) have

	Initial Start Conditions	Restart Conditions
Compression rate:	25,000 psi/s	50,000 psi/s
Compression ratio:	30:1	20:1
Test Temperature:	27 °C	135 °C
Gas Bubble:	Air/hvdrazine	Nitrogen/hydrazine


OBJECTIVES

- AFRL Required In-House capability to support new propellant development.
- Construct Adiabatic Compressibility System.
- Interface with computer (select A/D boards, I/O boards and low mV boards for thermocouples).
- Computer Program the system (using Labtech NoteBook).
- Three modes of operation:
- Valve calibration mode
- Actual adiabatic test mode for actual testing
- Continuous saving mode for regular maintenance
- Fulfill safety and environmental requirements.


Adiabatic Apparatus




Manifold and Pressurization System




Accumulator and Fast Acting Valve






Compression Chamber Location of Heating Bath 1-ton Jack (for -raising and lowering heating bath)


Computer Screen for LABTECH NoteBook Operating Program




Typical Example of a Positive Test




Typical Example of a Negative Test



Compression Rate in Presence of Rupture Disk



Compression Rate in Absence of Rupture Disk



Ruptured tube in a water bath New tube or after negative test

Severely damaged tubes in SS-ball bath




Table 1: Summary of Adiabatic Compression Results on Different Liquids

Test ID#	Sample	Temperature, °C	Temperature, °C Pressure, MPa (psi)	Result
1	Hydrazine	02	20.684 (3000)	ı
2	n-propyl nitrate	70	20.684 (3000)	
8	Nitromethane	0.2	20.684 (3000)	+
4	AFN (Batch 21)	20	20.684 (3000)	+
3	AFN (Batch 21)	25	20.684 (3000)	1

Table 2: Summary of Adiabatic Results Obtained on AFRL monopropellants

Test ID#	Sample	Temperature, °C	Pressure, MPa (psi)	Result
_	RK618A	15	13.79(2000)	+
7	RK618A	15	6.895 (1000)	+
В	RK618A	15	3.448 (500)	•
4	RK-100	100	20.684(3000)	•
S	RK-315E	15	13.79 (2000)	+
9	RK-315E	15	6.895 (1000)	+
7	RK-315E	15	3.448 (500)	1
∞	RK-315-A	15	20.684 (3000)	+
6	RK-315-A	15	13.79(2000)	+
10	RK-315-A	15	6.895 (1000)	ı

SUMMARY AND CONCLUSIONS

- A sturdy adiabatic compression apparatus has been constructed and successfully interfaced with a PC computer.
- A safe operating procedure has been established. Samples can be tested at temperatures up to 145 °C and at pressures up to 20.684 MPa (3000 psi).
- Typical rate of compressing rocket propellants is 120,000 psi/s. Maximum compression rate is 150,000 psi/s.
- Hydrazine is relatively stable to adiabatic compression when compared to other energetic liquids.
- All three propellants developed at AFRL passed the compressibility tests at a driving pressure ratio of 35/1.

ACKNOWLEDGEMENT

Mr. Greg Warmoth

Mr. Matt Jones

Mr. Adam Brand

Mr. Milton McKay

Mr. Tuong Chu Mr. Reginald Ching

Ms. Nicole Bauer

Mr. Rick Mahnick

Lt. Col. Scott Wierschke

Ms Carolyn Smith

Mr. Jeff Bean

MSgt Joseph Knallay

SSgt Richard Troxell